



100% MADE IN THE USA

GelBlack-GelWhite™

SUCTION LINE ONLY INSULATED LINESETS

APPLICATIONS

It provides the perfect lineset solution for unitary systems by combining a high-quality bare copper coil for the liquid line along with a perfectly pre-insulated suction line.

TECHNICAL SPECS

INSULATION

Low Density Polyethylene Closed Cell Foam

ASTM C 1427-07 compliant

Type I (tubular)

Grade I (insulation material for use on typical commercial system non-crosslinked)

CFC and HCFC gas free

Water vapor permeability: ASTM E96-00 compliant

Working temperature: ASTM C 1427-07 compliant from -94 F to +250 F

Wall thickness: 1/2" and 3/4"

Surface burning characteristics: UL 723 (ASTM E84 25/50) compliant, flame spread less than 25, smoke developed less than 50. UL 94 top rated.

R-Value: between 6.0 and 4.0 (depending on pipe diameter and insulation thickness)

UV Resistance: Successfully tested internally for UV resistance against any major degradation, discoloration or deterioration for a minimum of 5 years.

COPPER

Seamless copper tube for air conditioning and refrigeration.

Manufactured according to ASTM B280 C12200 DHP 99.9% pure.



SPECIAL FEATURES

Outer Jacket: Additional polyethylene jacket cover protects foam insulation from tearing during installation process.

Foot Marking: Insulation incrementally marked by every foot to ensure accurate initial unit charge and reduce copper waste.

R410: Can be used in applications where high-pressure gases are used as a refrigeration source.

Paintable: The insulation can be painted to match the surroundings.

Available Colors: Product available in black or white.



100% MADE IN THE USA

GelBlack-GelWhite™

SUCTION LINE ONLY INSULATED LINESETS

TRY IT, LOVE IT.

PDM US PART NUMBER (suction line only insulated)	SL	LL	INSULATION THICKNESS	LINE SETS PER PALLET	LENGTH OF COIL
GBW.UN385812050	3/8	5/8	1/2	14	50 FT
GBW.UN383412050	3/8	3/4	1/2	14	50 FT
GBW.UN387812050	3/8	7/8	1/2	12	50 FT
GBW.UN385812035	3/8	5/8	1/2	16	35 FT
GBW.UN383412035	3/8	3/4	1/2	16	35 FT
GBW.UN387812035	3/8	7/8	1/2	14	35 FT
GBW.UN385812030	3/8	5/8	1/2	18	30 FT
GBW.UN383412030	3/8	3/4	1/2	18	30 FT
GBW.UN387812030	3/8	7/8	1/2	16	30 FT
GBW.UN385812025	3/8	5/8	1/2	16	25 FT
GBW.UN383412025	3/8	3/4	1/2	16	25 FT
GBW.UN387812025	3/8	7/8	1/2	16	25 FT
GBW.UN385834050	3/8	5/8	3/4	8	50 FT
GBW.UN383434050	3/8	3/4	3/4	8	50 FT
GBW.UN387834050	3/8	7/8	3/4	8	50 FT
GBW.UN385834035	3/8	5/8	3/4	12	35 FT
GBW.UN383434035	3/8	3/4	3/4	10	35 FT
GBW.UN387834035	3/8	7/8	3/4	10	35 FT
GBW.UN385834030	3/8	5/8	3/4	10	30 FT
GBW.UN383434030	3/8	3/4	3/4	10	30 FT
GBW.UN387834030	3/8	7/8	3/4	8	30 FT
GBW.UN385834025	3/8	5/8	3/4	10	25 FT
GBW.UN383434025	3/8	3/4	3/4	10	25 FT
GBW.UN387834025	3/8	7/8	3/4	8	25 FT