



## Material Data Sheet Rev 8.22 (08/22/22)



**Product Name:** GEL29 Copper Tube

**Copper:** copper tube manufactured according to ASTM B280, ASME B35 and ANSI B9.1 refrigeration industry standards.

**Copper Alloy N.** C12200

**CU %** 99.9

**P %:** 0.015 to 0.040

**Temper:** 060

**Tensile Strength:** 205 MPa (30.0 ksi Min)

**Elongation %:** >40

**Expansion Test:** Min 40%

## **Declaration of NO RED List Items:**

PDM US LLC declares all its products to be cleared of all the RED LIST ITEMS, specifically:

- Asbestos • Cadmium • Chlorinated Polyethylene and Chlorosulfonated Polyethylene
- Chlorofluorocarbons (CFCs) • Chloroprene (Neoprene) • Formaldehyde (added)
- Halogenated Flame Retardants • Hydro chlorofluorocarbons (HCFCs) • Lead (added)
- Mercury • Petrochemical Fertilizers and Pesticides • Phthalates • Polyvinyl Chloride (PVC)
- Wood treatments containing Creosote, Arsenic or Pentachlorophenol

## **California Proposition 65 Declaration**

All PDM US LLC products do NOT contain chemicals listed on California's Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

**All PDM products are 100% recyclable**

### **PDM US LLC**

640 Cel River road Rock Hill 29730 USA  
PH: (803) 909-8100 Fax: (803) 909-8725

[www.pdmus.com](http://www.pdmus.com)  
[info@pdmus.com](mailto:info@pdmus.com)