

## Material Data Sheet Rev 0323



**Product Name:** GEL29 Copper Tube

**Copper:** copper tube manufactured according to ASTM B280 / ASTM B1003 - C12200 DHP - 700 PSI - 99.9% pure

**Copper Alloy N.** C12200

**CU %** 99.9

**P %:** 0.015 to 0.040

**Temper:** 060

**Tensile Strength:** 205 MPa (30.0 ksi Min)

**Elongation %:** >40

**Expansion Test:** Min 40%

## **Declaration of NO RED List Items:**

PDM US LLC declares all its products to be cleared of all the RED LIST ITEMS, specifically:

- Asbestos • Cadmium • Chlorinated Polyethylene and Chlorosulfonated Polyethylene
- Chlorofluorocarbons (CFCs) • Chloroprene (Neoprene) • Formaldehyde (added)
- Halogenated Flame Retardants • Hydro chlorofluorocarbons (HCFCs) • Lead (added)
- Mercury • Petrochemical Fertilizers and Pesticides • Phthalates • Polyvinyl Chloride (PVC)
- Wood treatments containing Creosote, Arsenic or Pentachlorophenol

## **California Proposition 65 Declaration**

All PDM US LLC products do NOT contain chemicals listed on California's Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

**All PDM products are 100% recyclable**

**All PDM products are in full compliance with the BABA Act**

