



100% MADE IN THE USA



GelCopper[®] Ductless Line Sets

PREINSULATED COPPER ROLLS

APPLICATIONS

GelCopper[®] Ductless Line Sets provide the perfect size combination for applications requiring both suction and liquid lines to be insulated, such as mini-splits, VRF and heat pumps.

TECHNICAL SPECS

INSULATION

Low Density Polyethylene Closed Cell Foam
ASTM C 1427-07 compliant
Type I (tubular)
Grade I (insulation material for use on typical commercial system non-crosslinked)
CFC and HCFC gas free
ASME B35.1 and ANSI B9.1 compliant
Water vapor permeability: ASTM E96-00 compliant
Working temperature: ASTM C 1427-07 compliant from -94 F to +250 F
Wall thickness: 1/2"
Surface burning characteristics: **UL723 CERTIFIED R39562** (ASTM E84 25/50), surface burning characteristics: flame spread 0, smoke developed 10. UL 94, top rated.
R-Value: 4.0
UV: This product is **UL PERFORMANCE VERIFIED** for UV resistance and successfully tested internally for UV resistance against any major degradation, discoloration or deterioration for a minimum of 5 years.

COPPER

Made in USA seamless anti corrosion copper tube for air conditioning and refrigeration. Manufactured according to ASTM B280 / ASTM B1003 - C12200 DHP - 700 PSI - 99.9% pure.



SPECIAL FEATURES

Anti-Corrosion Copper: Cu29BA patent pending technology provides strong anticorrosion properties to copper tubes reducing any risk of formicary/pitting corrosion.
Outer Jacket: Additional polyethylene jacket cover protects foam insulation from tearing during installation process.
Foot Marking: Insulation incrementally marked every foot to reduce copper waste and ensure accurate initial unit charge.
R410 and R454B: Can be used in applications where high-pressure gases are used as a refrigeration source.
Colors: Available in black or white insulation.
Paintable: The insulation can be painted to match the surroundings.



100% MADE IN THE USA



GelCopper[®] Ductless Line Sets

PREINSULATED COPPER ROLLS

TRY IT, LOVE IT[®]

PRODUCT TABLE

PDM [®] PART NUMBER (both lines insulated)	LL	SL	INSULATION	LINE SETS (per pallet)	LENGTH OF COIL (FT)
F100.LSIN143812025	1/4	3/8	1/2	18	25
F100.LSIN141212025	1/4	1/2	1/2	16	25
F100.LSIN145812025	1/4	5/8	1/2	14	25
F100.LSIN385812025	3/8	5/8	1/2	14	25
F100.LSIN383412025	3/8	3/4	1/2	14	25
F100.LSIN387812025	3/8	7/8	1/2	12	25
F100.LSIN143812035	1/4	3/8	1/2	14	35
F100.LSIN141212035	1/4	1/2	1/2	14	35
F100.LSIN145812035	1/4	5/8	1/2	10	35
F100.LSIN385812035	3/8	5/8	1/2	10	35
F100.LSIN383412035	3/8	3/4	1/2	10	35
F100.LSIN387812035	3/8	7/8	1/2	8	35
F100.LSIN143812050	1/4	3/8	1/2	12	50
F100.LSIN141212050	1/4	1/2	1/2	10	50
F100.LSIN145812050	1/4	5/8	1/2	8	50
F100.LSIN385812050	3/8	5/8	1/2	8	50
F100.LSIN383412050	3/8	3/4	1/2	8	50
F100.LSIN387812050	3/8	7/8	1/2	8	50

Pallet quantities subject to change without notice.